



NTN Bearing de Mexico, S.A.

17 mm x 40 mm x 21 mm SKF NUTR 17 X Cam Follower and Track Roller - Yoke Type



NUTR 17 X Bearing 2D drawings and 3D CAD models

Bearing No. NUTR 17 X

| | |
|------------------------|---|
| Category | Cam Follower and Track Roller - Yoke Type |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.15 |
| EAN | 7316577105066 |
| Product Group | B04144 |
| Roller Surface Profile | Flat |
| Profile | Yoke Type |
| Enclosure | Sealed |
| Rolling Element | Cylindrical Roller Bearing - Double Row |
| Relubricatable | Yes |
| Inch - Metric | Metric |
| Other Features | Full Complement With Flanged Inner Ring Labyrinth Seal |
| Long Description | 17MM Bore; 40MM Roller Diameter; 20MM Roller Width; Flat Roller; Yoke Type; Sealed; Cylindrical Roller Bearing - Double Row; Relubricatable |
| Category | Cam Followers Yoke Type |
| UNSPSC | 31171530 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| | |



NTN Bearing de Mexico, S.A.

| | |
|--|---|
| Keyword String | Cam Follower |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | NUTR 17 X |
| Weight / LBS | 0.331 |
| d | 0.669 Inch 17 Millimeter |
| Roller Diameter | 1.575 Inch 40 Millimeter |
| Roller Width | 0.787 Inch 20 Millimeter |
| D | 40 mm |
| d | 17 mm |
| C | 20 mm |
| B | 21 mm |
| d ₁ | 22 mm |
| r _{1,2} min. | 1 mm |
| r, r _{3,4} min. | 0.5 mm |
| Basic dynamic load rating C | 19 kN |
| Basic static load rating C ₀ | 22 kN |
| Fatigue load limit P _u | 2.5 kN |
| Maximum dynamic radial loads F _r max. | 14 kN |
| Maximum static radial loads F _{0r} max. | 20 kN |
| Limiting speed | 4500 r/min |
| Mass support roller | 0.15 kg |