



# NTN Bearing de Mexico, S.A.



## 25 mm x 62 mm x 25 mm SKF NUTR 2562 A Cam Follower and Track Roller - Yoke Type

Bearing No. NUTR 2562 A

NUTR 2562 A Bearing 2D drawings and 3D CAD models

Category	Cam Follower and Track Roller - Yoke Type
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.45
EAN	7316570169874
Product Group	B04120
Roller Surface Profile	Crowned
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing - Double Row
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Full Complement   With Flanged Inner Ring   Labyrinth Seal
Long Description	25MM Bore; 62MM Roller Diameter; 24MM Roller Width; Crowned Roller; Yoke Type; Sealed; Cylindrical Roller Bearing - Double Row; Relubricatable
Category	Cam Followers Yoke Type
UNSPSC	31171530
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing



## NTN Bearing de Mexico, S.A.

Keyword String	Cam Follower
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NUTR 2562 A
Weight / LBS	0.992
Roller Diameter	2.441 Inch   62 Millimeter
Roller Width	0.945 Inch   24 Millimeter
d	0.984 Inch   25 Millimeter
roller diameter:	62 mm
radial dynamic load capacity:	35.8 kN
roller width:	24 mm
radial static load capacity:	48 kN
bore diameter:	25 mm
roller material:	Steel
roller shape:	Crowned
maximum rpm:	3200 rpm
bearing element:	Cylindrical Rollers
finish/coating:	Uncoated
overall width:	25 mm
manufacturer catalog:	<a href="#">Click here</a>
closure type:	Sealed
series:	NUTR
operating temperature range:	300 ° F
manufacturer upc number:	7316570169874
D	62 mm
d	25 mm
C	24 mm
B	25 mm
d <sub>1</sub>	31 mm
r <sub>1,2</sub> min.	1 mm
r, r <sub>3,4</sub> min.	0.5 mm
Basic dynamic load rating C	35.8 kN



## NTN Bearing de Mexico, S.A.

Basic static load rating $C_0$	48 kN
Fatigue load limit $P_u$	5.6 kN
Maximum dynamic radial loads $F_r$ max.	44 kN
Maximum static radial loads $F_{0r}$ max.	63 kN
Limiting speed	3200 r/min
Mass support roller	0.45 kg